



KONICA MINOLTA

bizhub 4750/4050/4020/3320 Spec Sheet


System

bizhub 4750/4050

- **i-Option LK-101 v3**
Web browse function
- **i-Option LK-106**
Barcode font
(Code39, QR Code, PDF417)
- **i-Option LK-107**
Unicode font
- **i-Option LK-108**
OCR font (OCR-A, OCR-B (PCL))
- **i-Option LK-111**
ThinPrint function
- **Keypad KP-P01**
- **Local Interface Kit EK-P04**
RS232C (for CSRC) cable
- **Network Interface Card NC-P03**
802.11b/g/n Wireless

bizhub 4020/3320

- **Upgrade kit UK-P01**
256 MB User Flash
- **Upgrade kit UK-P04**
Korean Font Card
- **Upgrade kit UK-P05**
Simplified Chinese Font Card
- **Upgrade kit UK-P06**
Traditional Chinese Font Card
- **Upgrade kit UK-P07**
Japanese Font Card
- **Upgrade kit UK-P10**
Forms and Barcode Card
* for bizhub 4020
- **Upgrade kit UK-P11**
IPDS Card
* for bizhub 4020
- **Expanded Memory Unit EM-P03**
2 GB
* for bizhub 4020
- **Expanded Memory Unit EM-P04**
1 GB
* for bizhub 4020
- **Network Interface Card NC-P02**
802.11b/g/n Wireless
* for bizhub 4020
- **Network Interface Card NC-P03**
802.11b/g/n Wireless
* for bizhub 3320
- **Local Interface Kit EK-P02**
IEEE 1284-B Parallel Card
* for bizhub 4020
- **Local Interface Kit EK-P03**
RS232C Serial Card
* for bizhub 4020



Specifications

bizhub 4750/4050 General Specifications

		bizhub 4750	bizhub 4050	
Type	Desktop Printer / Copier / Scanner			
Copy Resolution	Scan	Main: 600 dpi × Sub: 600 dpi		
	Print	Main: 600 dpi × Sub: 600 dpi		
Gradation	256			
Memory Capacity (Std./Max.)	2 GB / 2 GB			
HDD	320 GB			
Original Type	Sheets, Books, Objects			
Max. Original Size	A4 or Legal (8-1/2" × 14")			
Output Size	Legal, Letter, A4 to A6, Custom: 76.2 × 127 mm to 216 × 356 mm			
Image Loss	Copy	Max. 4.0 mm ±2 mm for top / bottom / right / left edges		
	Print	Max. 4.2 mm ±2 mm or less for top / bottom / right / left edges		
Warm-Up Time*1	77 sec. or less			
First Copy Out Time*2	8.5 sec. or less			
Copy Speed (A4)		47 ppm	40 ppm	
	Copy Magnification	1: 1.000		
Paper Capacity (75 g/m ²)	Tray 1	550 sheets (up to Legal)		
	Multiple Bypass Tray	100 sheets (up to Legal)		
	Max. Paper Capacity (75 g/m ²)	2,300 sheets		
	Paper Weight	Tray 1	60 to 120 g/m ²	
		Multiple Bypass Tray	60 to 163 g/m ²	
	Multiple Copy	1 to 999 sheets		
Auto Duplex	Type	Non-Stack		
	Paper Size	Legal, Letter, A4		
	Paper Weight	60 to 90 g/m ²		
Power Requirements	AC220 to 240 V 4.2 A (50 to 60 Hz)			
Max. Power Consumption	972 W or less	926 W or less		
Dimensions [W] × [D] × [H]	489 × 482 × 561 mm (19-1/4" × 19" × 22")			
Weight	Approx. 24 kg (52 lb)			
Space Requirements*3 [W] × [D]	669 × 886.8 mm (26-1/4" × 35")			

*1 Warm-up time may vary depending on the operating environment and usage.
The time required to start printing when both the main power and sub-power switches are turned from OFF to ON. (23°C, std. voltage)

*2 A4 full size/using the first tray/scanning from the original glass surface.

*3 Without options, with paper trays pulled out, and multiple bypass tray, auxiliary tray and ADF opened.

Printer Specifications

Type	Embedded		
CPU	88PA6170 (800 MHz)		
Memory	Shared with the copier		
Print Speed	Same as Copy Speed (when using the same original)		
HDD	320 GB (Shared with the copier)		
Print Resolution	Default mode: 600 dpi × 600 dpi		
	High Quality mode*1: 1,200 dpi × 1,200 dpi		
PDL	PCL 5e/c Emulation, PCL 6 Emulation, PostScript3 (3016) Emulation, XPS (Ver.1.0), PPML/GA2.2, PPML VDX, OpenXPS, PDF1.7, OOXML(docx, xlsx, pptx)		
Protocol	TCP/IP, LPD, IPP1.1, HTTP, WSD		
Support OS	PCL	Windows Vista (x32, x64) / 7 (x32, x64) / 8 (x32, x64) / 8.1 (x32, x64)	
		Windows Server 2003 (x32, x64) / Server 2008 (x32, x64) / Server 2012 (x32, x64)	
	PS	Windows Vista (x32, x64) / 7 (x32, x64) / 8 (x32, x64) / 8.1 (x32, x64)	
	XPS	Windows Vista (x32, x64) / 7 (x32, x64) / 8 (x32, x64) / 8.1 (x32, x64)	
		Windows Server 2003 (x32, x64) / Server 2008 (x32, x64) / Server 2012 (x32, x64)	
Fonts	PCL	80 Roman fonts	
	PS	137 Roman Type1 fonts	
Interface	Ethernet (10BASE-T / 100BASE-TX / 1000BASE-T), USB 1.1, USB 2.0		

*1 Output speed will be reduced.

Scanning Specifications

Type	Full-Colour Scanner		
Interface	Ethernet (10BASE-T / 100BASE-TX / 1000BASE-T)		
Driver	TWAIN Driver		
Protocol	TCP/IP (FTP, SMB, SMTP, WebDAV), TCP Socket WSD		
Scanning Speed (A4, 300 dpi)	B&W/Colour: 45/30 opm		
Scanning Size	Max. A4 or Legal (8-1/2" × 14")		
Output Format	TIFF, JPEG, PDF, Compact PDF, XPS, PDF/A		
Scanning Resolution	Push	200 dpi / 300 dpi / 400 dpi / 600 dpi	
	Pull	200 dpi / 300 dpi / 400 dpi / 600 dpi	
Main Functions	Scan to E-Mail, Scan to FTP, Scan to BOX (HDD), Scan to PC (SMB), Network TWAIN, Scan to WebDAV, Scan to USB, WSD Scan		

Reverse Automatic Document Feeder

		bizhub 4750	bizhub 4050
Type	Circulatory duplex system		
Support Paper Size	Legal, Letter, A4 to A6, Custom: 105 × 148 mm to 216 × 356 mm		
Mixed Size	Support		
Original Set	Centre guide		
Resolution	600 dpi support		
Support Paper Weight	52 to 120 g/m ²		
Paper Capacity (75 g/m ²)	Max. 50 sheets		
Productivity (A4)	Simplex	Copy	B&W: 47 opm
		Scan	B&W: 45 opm, Colour: 30 opm
	Duplex	Copy	B&W: 20 opm
		Scan	B&W: 20 opm, Colour: 13 opm

Fax Kit FK-512 (Optional)

Communication	Super G3
Compatible Lines	Public Switch Telephone Network, Private Branch Exchange, Fax Communication Line
Line Density	G3 (8 dot/mm × 3.85 line/mm, 600 × 600 dpi)
Modem Speed	2.4 to 33.6 kbps
Compression	MH / MR / MMR / JBIG
Sending Paper Size	Max. A4 or Legal (Long Length Support: Max. 1,000 mm (ADF))
Recording Paper Size	Max. A4 or Legal (Long Length Max. 1,000 mm — following the page division —)
Transmission Speed	Less than 3 sec. (A4, V34, 33.6 kbps, JBIG)
Memory	Shared with the copier
Number of Abbr. Dials	2,000
Number of Group Dials	100
Sequential Multiple Station Transmission	Max. 400

Internet Fax (Optional) *Optional Fax Kit FK-512 is required.

Protocol	SMTP, POP
Connection Mode	Full-Mode
Sending Paper Size	Max. A4 or Legal
Recording Paper Size	Max. Legal
Resolution	200 × 100 dpi, 200 × 200 dpi, 400 × 400 dpi, 600 × 600 dpi
Interface	Ethernet (10BASE-T / 100BASE-TX / 1000BASE-T)
Format	Send: TIFF-F, Receive: TIFF-F

Finisher FS-P02 (Optional)

Type	Stapler
Support Paper Size	A4, Letter, Legal
Mode	Corner staple
Staple Capacity	20 sheets (75 g/m ²)
Dimensions [W] × [D] × [H]	410 × 370 × 195 mm (15-1/4" × 14-1/2" × 7-3/4") (The depth of the finisher includes the projecting parts.)
Weight	Approx. 5.3 kg (11.6 lb)

Paper Feeder Unit PF-P11 (Optional)

Support Paper Type (Weight)	60 to 120 g/m ²
Support Paper Size	Legal, Letter, A4, B5, A5 Custom: 105 × 148 mm to 216 × 356 mm
Paper Capacity (75 g/m ²)	250 sheets
Power Requirements	Supplied from the MFP main body
Dimensions [W] × [D] × [H]	389 × 382 × 77 mm (15-1/4" × 15" × 3")
Unit Configuration	Paper tray, 1 level
Weight	Approx. 4.2 kg (9-1/4 lb)

Paper Feeder Unit PF-P12 (Optional)

Support Paper Type (Weight)	60 to 120 g/m ²
Support Paper Size	Legal, Letter, A4, B5, A5 Custom: 105 × 148 mm to 216 × 356 mm
Paper Capacity (75 g/m ²)	550 sheets
Power Requirements	Supplied from the MFP main body
Dimensions [W] × [D] × [H]	389 × 382 × 109 mm (15-1/4" × 15" × 4-1/4")
Unit Configuration	Paper tray, 1 level
Weight	Approx. 4.7 kg (10-1/4 lb)

Authentication Unit (IC Card type) AU-201 (Optional)

Applicable Card	ISO 14443 TypeA, FeliCa-based noncontact IC card
Interface	USB 1.1 or later
Power Supply	Power received from USB port
Dimensions [W] × [D] × [H]	92 × 64 × 16 mm (3-3/4" × 2-1/2" × 3/4")
Weight	Approx. 120 g (264-1/2 lb)



bizhub 4750 + PF-P11 + PF-P12

Specifications

bizhub 4020/3320 General Specifications

		bizhub 4020	bizhub 3320
Type		Desktop Printer / Copier / Scanner	
Copy Resolution	Scan	Main: 600 dpi × Sub: 600 dpi	
	Print	Main: 600 dpi × Sub: 600 dpi	
Gradation		256	
Memory Capacity (Std./Max.)		512 MB / 2.5 GB	256 MB / 256 MB
HDD		160 GB (Opt.)	—
Original Type		Sheets, Books, Objects	
Max. Original Size		A4 or Legal (8-1/2" × 14")	
Output Size		Legal, Letter, A4 to A6 Custom: 76.2 × 127 mm to 216 × 356 mm	
Image Loss	Copy	Max. 4.0 mm ±0.2 mm or less for top/bottom/right/left edges	
	Print	Max. 4.0 mm ±0.2 mm or less for top/bottom/right/left edges	
Warm-Up Time*1		95 sec. or less	76 sec. or less
First Copy Out Time*2		6.5 sec. or less	
Copy Speed (A4)		40 ppm	33 ppm
Copy Magnification	Fixed Same Magnification	1: 1.000 ±0.5% or less	
	Scaling Up	1: 1.15 / 1.22 / 1.41	
	Scaling Down	1: 0.87 / 0.82 / 0.70	
	Preset	3 types	
	Zoom	25 to 400% (in 1% increments)	
Paper Capacity (75 g/m ²)	Tray 1	250 sheets (up to Legal)	
	Multiple Bypass Tray	100 sheets (up to Legal)	50 sheets (up to Legal)
Max. Paper Capacity (75 g/m ²)		2,000 sheets	
Paper Weight	Tray 1	60 to 120 g/m ²	
	Multiple Bypass Tray	60 to 163 g/m ²	
Multiple Copy		1 to 999 sheets	
Auto Duplex	Type	Non-Stack	
	Paper Size	Legal, Letter, A4	
	Paper Weight	60 to 90 g/m ²	
Power Requirements		AC220 to 240 V 4.0 A (50 to 60 Hz)	
Dimensions [W] × [D] × [H]		489 × 452 × 502 mm (19-1/4" × 17-3/4" × 19-3/4")	389 × 472 × 468 mm (15-1/4" × 18-1/2" × 18-1/2")
Weight		Approx. 21.8 kg (48 lb)	
Space Requirements*3 [W] × [D]		664 × 856.8 mm (26-1/4" × 33-3/4")	564 × 876.8 mm (22-1/4" × 34-1/2")

*1 Warm-up time may vary depending on the operating environment and usage.
The time required to start printing when both the main power and sub-power switches are turned from OFF to ON. (23°C, std. voltage)

*2 A4 full size/using the first tray/scanning from the original glass surface.

*3 Without options, with paper trays pulled out, and multiple bypass tray, auxiliary tray and ADF opened.

Fax Specifications

Communication	Super G3
Compatible Lines	Public Switch Telephone Network, Private Branch Exchange, Fax Communication Line
Line Density	G3 (8 dot/mm × 3.85 line/mm, 600 × 600 dpi)
Modem Speed	2.4 to 33.6 kbps
Compression	MH / MR / MMR / JBIG
Sending Paper Size	Max. A4 or Legal
Recording Paper Size	Max. A4 or Legal
Transmission Speed	Less than 3 sec. (A4, V34, 33.6 kbps, JBIG)
Memory	Shared with the copier
Number of Abbr. Dials	500
Sequential Multiple Station Transmission	Max. 400

Reverse Automatic Document Feeder (For bizhub 4020)

Type	Circulatory duplex system		
Support Paper Size	Legal, Letter, A4 to A6 Custom: 105 × 148 mm to 216 × 356 mm		
Mixed Size	Support		
Original Set	Centre guide		
Resolution	600 dpi support		
Support Paper Weight	52 to 120 g/m ²		
Paper Capacity (75 g/m ²)	Max. 50 sheets		
Productivity (A4)	Simplex	Copy	B&W: 40 opm
		Scan	B&W: 41 opm, Colour: 19 opm
	Duplex	Copy	B&W: 18 opm
		Scan	B&W: 18 opm, Colour: 8 opm

Automatic Document Feeder (For bizhub 3320)

Type	Simplex system		
Support Paper Size	Legal, Letter, A4 to A6 Custom: 105 × 148 mm to 216 × 356 mm		
Mixed Size	Support		
Original Set	Centre guide		
Resolution	600 dpi support		
Support Paper Weight	52 to 120 g/m ²		
Paper Capacity (75 g/m ²)	Max. 50 sheets		
Productivity (A4)	Simplex	Copy	B&W: 33 opm
		Scan	B&W: 42 opm, Colour: 19 opm
	Duplex	Scan	B&W: 42 opm, Colour: 19 opm

Printer Specifications

		bizhub 4020	bizhub 3320
Type		Embedded	
CPU		6170 (800 MHz)	
Memory		Shared with the copier	
Print Speed		Same as Copy Speed (when using the same original)	
HDD		Shared with the copier	
Print Resolution		Default mode: 600 dpi × 600 dpi High Quality mode *1: 1,200 dpi × 1,200 dpi Enhanced mode *1: 2,400 dpi equiv.	
PDL		PCL5 Emulation, PCL6 Emulation, PostScript3 Emulation, XPS	
Protocol		TCP/IP, IPP1.1, SNMP, HTTP	
Support OS	PCL	Windows Vista (x32, x64) / 7 (x32, x64) / 8 (x32, x64) / 8.1 (x32, x64) Windows Server 2003 (x32, x64) / Server 2008 (x32, x64) / Server 2012 (x32, x64)	
	PS	Windows Vista (x32, x64) / 7 (x32, x64) / 8 (x32, x64) / 8.1 (x32, x64) Windows Server 2003 (x32, x64) / Server 2008 (x32, x64) / Server 2012 (x32, x64) Mac OS X 10.6 / X 10.7 / X 10.8 / X 10.9 Linux	
	XPS	Windows Vista (x32, x64) / 7 (x32, x64) / 8 (x32, x64) / 8.1 (x32, x64) Windows Server 2008 (x32, x64) / Server 2012 (x32, x64)	
Fonts	PCL	89 Roman fonts	
	PS	91 Roman Type1 fonts	
Interface		Ethernet (10BASE-T / 100BASE-TX / 1000BASE-T), USB 2.0, USB Host, IEEE1284 (Opt.)	Ethernet (10BASE-T / 100BASE-TX), USB 2.0

*1 Output speed will be reduced.

Scanning Specifications

		bizhub 4020	bizhub 3320
Type		Full-Colour Scanner	
Interface		Ethernet (10BASE-T / 100BASE-TX)	
Driver		TWAIN Driver	
Protocol		TCP/IP (FTP, SMB, SMTP)	
Scanning Speed (A4, 300 dpi)	Simplex	B&W/Colour: 41/19 opm	
	Duplex	B&W/Colour: 18/8 opm	
Scanning Size		Max. A4 or Legal (8-1/2" × 14")	Max. A4 or Letter
Output Format		TIFF, JPEG, PDF, XPS	
Scanning Resolution	Push	200 dpi / 300 dpi / 400 dpi / 600 dpi	
	Pull	200 × 100 dpi / 300 dpi / 400 dpi / 600 dpi	
Main Functions		Scan to E-Mail, Scan to FTP, Network TWAIN, Scan to USB, Scan to Web Service (WSD Scan), Device Profile for Web Services (DPWS)	Scan to E-Mail, Scan to FTP, Network TWAIN, Scan to Web Service (WSD Scan), Device Profile for Web Services (DPWS)
Other Functions		Multi-Method Send, Authentication at the time of E-Mail send (SMTP authentication, POP before SMTP)	

Paper Feeder Unit PF-P11 (Optional)


Support Paper Type (Weight)	60 to 120 g/m ²
Support Paper Size	Legal, Letter, A4, B5, A5 Custom: 105 × 148 mm to 216 × 356 mm
Paper Capacity (75 g/m ²)	250 sheets
Power Requirements	Supplied from the MFP main body
Dimensions [W] × [D] × [H]	389 × 382 × 77 mm (15-1/4" × 15" × 3")
Unit Configuration	Paper tray, 1 level
Weight	Approx. 4.2 kg (9-1/4 lb)

Paper Feeder Unit PF-P12 (Optional)


Support Paper Type (Weight)	60 to 120 g/m ²
Support Paper Size	Legal, Letter, A4, B5, A5 Custom: 105 × 148 mm to 216 × 356 mm
Paper Capacity (75 g/m ²)	550 sheets
Power Requirements	Supplied from the MFP main body
Dimensions [W] × [D] × [H]	389 × 382 × 109 mm (15-1/4" × 15" × 4-1/4")
Unit Configuration	Paper tray, 1 level
Weight	Approx. 4.7 kg (9-1/4 lb)




bizhub 4020 + 3 × PF-P12




Front View
bizhub 4750/4050




Side View
bizhub 4750/4050




Front View
bizhub 4020



Side View
bizhub 4020



Front View
bizhub 3320



Side View
bizhub 3320